


Technical data

Duropal Compact Worktop, white core

Compact high pressure laminate with single or double-sided machined longitudinal edge in standard quality according to EN 438-9:BCS for use as a worktop. With uniform white-coloured core, single-sided decorative melamine resin surface and decorative backing.




Specification			Unit	Standard
Nominal thickness	12	12	mm	
Length	4,100	4,100	mm	
Width	640	950	mm	
Design front edge		chamfered		
Design rear edge	milled		chamfered	
Tolerance on thickness		± 0.8	mm	EN 438-2:2016
Tolerance on length		+ 10	mm	EN 438-2:2016
Tolerance on width	± 0.6		mm	EN 13894-1
tolerance on edge processing		± 0.2	mm	
Surface defects (Product top side / usable Surface)		max. 1 ¹⁾ max. 10 ²⁾	mm ² /m ² mm/m ²	EN 438-9:2017
Surface defects (Texture CM, GR, RC)	Please note that both handling and also general use of the material can lead to a polishing effect in the surface structure, something which is most apparent.			
Edge defects (Head edge)		max. 3	mm	EN 438-9:2017
Straightness of edges		± 0.5	mm/m	EN 13894-1
Squareness		max. 2	mm/m	EN 13894-1
Flatness		max. 5	mm	EN 438-2:2016
Density		min. 1,400	kg/m ³	EN ISO 1183-1
Bending strength		min. 80	MPa	EN ISO 178
Flexural modulus		min. 9,000	MPa	EN ISO 178
Resistance to crazing		min. 3 ³⁾ min. 4 ⁴⁾	rating	EN 438-2:2016
Dimensional stability at elevated temperature (length)		max. 0.5	%	EN 438-2:2016
Dimensional stability at elevated temperature (width)		max. 0.8	%	EN 438-2:2016
Resistance to dry heat, 160 °C (smooth finishes)		min. 3	rating	EN 438-2:2016
Resistance to dry heat, 160 °C (textured finishes)		min. 4	rating	EN 438-2:2016
Resistance to water vapour (smooth finishes)		min. 3	rating	EN 438-2:2016
Resistance to water vapour (textured finishes)		min. 4	rating	EN 438-2:2016
Resistance to immersion in boiling water (smooth finishes)		min. 3	rating	EN 438-2:2016
Resistance to immersion in boiling water (textured finishes)		min. 4	rating	EN 438-2:2016
Resistance to immersion in boiling water (edge)		min. 3	rating	EN 438-2:2016
Resistance to immersion in boiling water		max. 3 ⁵⁾ max. 4 ⁶⁾	%	EN 438-2:2016
Resistance to surface wear		min. 150	cycles	

Technical data

Duropal Compact Worktop, white core

Compact high pressure laminate with single or double-sided machined longitudinal edge in standard quality according to EN 438-9:BCS for use as a worktop. With uniform white-coloured core, single-sided decorative melamine resin surface and decorative backing.



Specification			Unit	Standard
Nominal thickness	12	12	mm	
Length	4,100	4,100	mm	
Width	640	950	mm	
Resistance to scratching (smooth finishes)	min. 2		rating	EN 438-2:2016
Resistance to scratching (textured finishes)	min. 3		rating	EN 438-2:2016
Stain resistance (groups 1 & 2)	min. 5		rating	EN 438-2:2016
Stain resistance (group 3)	min. 4		rating	EN 438-2:2016
Resistance to colour change (xenon arc light)	min. 3 Grey Scale Grade ³⁾ min. 4 Grey Scale Grade ⁴⁾			EN 438-2:2016
Reaction to fire	normally flammable			
Reaction to fire (Euroclass)	D-s2,d0			EN 13501-1, CWFT acc. to 2003/593/EG
Formaldehyde emission class	E1			

- ¹⁾ Dirt, spots and similar surface defects
²⁾ Fibres, hairs and scratches
³⁾ Edge/Core
⁴⁾ Texture
⁵⁾ Mass increase
⁶⁾ Thickness increase


Additional information

Product standard	<ul style="list-style-type: none"> EN 438-9
Areas of application	<ul style="list-style-type: none"> In all private and public interior application areas in which robustness, long durability, and high hygienic demands are placed on the Duropal Compact Worktop, such as in hotels and restaurants, shops, sanitary areas, schools, sports facilities and swimming pools.
Core material	<ul style="list-style-type: none"> Compact laminate white Homogeneous white through-pigmented solid compact laminate core, impact resistant and moisture resistant for applications with high specification demands.
Product safety	<ul style="list-style-type: none"> The surface is physiologically safe, and approved for direct contact with food acc. to Regulation (EU) No. 10/2011. The decorative surface and the core consists of paper layers that are impregnated with thermosetting resins. The resins harden completely during the manufacturing process by heat and high pressure. They form a stable, resistant and non-reactive material. This product follows the REACH regulation EC 1907/2006 an article. Following Article 7 it does not need to be registered.
Packaging	<ul style="list-style-type: none"> Duropal Compact Worktops are delivered exclusively in individual cardboard packaging. The top / usable surface of the product is labelled in the factory. Packaged on pallets (colli).

Technical data

Duropal Compact Worktop, white core

Compact high pressure laminate with single or double-sided machined longitudinal edge in standard quality according to EN 438-9:BCS for use as a worktop. With uniform white-coloured core, single-sided decorative melamine resin surface and decorative backing.



Special

- Due to the white core of the material, minor decorative deviations to other products cannot be avoided.
- For production-related reasons, there may be minor colour variations in the white material core.
- Due to the material core, Duropal Compact Worktops with a white core are slightly harder and more brittle than Compact Worktops with a black material core. These will tend to warp more severely in case of climatic fluctuations.
- Depending on the decor and surface texture, slightly different surface visual impressions can result between cut panels viewed from different angles. This is a result of the production methods and does not constitute a quality defect.
- With PEFC-certification (license code: PEFC/04-32-0828).
- Due to the processing (chamfer, grind and saw) slight colour variations of the coloured material core may occur.
- Please note that polishing, scratches and shine marks can occur in everyday use. This is caused by the product and does not represent a quality defect. Traces of use can be minimized by subsequent oiling of the edge. Further information can be found in our processing recommendation "Duropal Compact Worktop".
- Certificate Blue Angel - Ecolabel (RAL DE-UZ 76)
- The material must not be exposed to heat influences by light- or heat radiation which will increase the surface temperature to more than 50°C.
- Duropal Compact Worktop, white core is not supplied with protective foil.
- Decor-structure-combination front side = Decor-structure-combination reverse side
- The coarser the structure and the lighter the decor, the greater the scratch resistance.
- The smoother the structure and the darker the decor, the more sensitive it is to stains.
- Especially for large applications, we recommend paying attention to the colour and texture uniformity of the boards and cut products used when further processing and installing and that the production direction is taken into account.

© Copyright 2020 Pfleiderer Deutschland GmbH / Pfleiderer Polska sp. z o.o.

This information has been compiled with the greatest care. Nevertheless we can assume no liability for the correctness, completeness and up-to-date-ness of this information. Colour deviations caused by the printing technology are possible. In view of the ongoing further development and adaptation of our products, possible amendments to the relevant standards, laws and regulations, our technical data sheets and product documentation expressly do not constitute a legally binding assurance of the properties described there. In particular no guarantee of suitability for a concrete application can be derived. It is therefore the personal responsibility of the individual user in all cases to check the processing and suitability of the products described in this document for the intended application in advance, and to take into consideration the legal framework and the respective state-of-the-art. We furthermore expressly draw attention to the applicability of our General Terms and Conditions.