

Manufacturer	<p>Pfleiderer Wieruszów sp. z o. o. Bolesławiecka 10 St, 98-400 Wieruszów tel. +48 62 78 33 100</p>
Product description	<p>Duropal-HPL. Countertops and interior design elements - wood-based panel refined by wrapping: a working surface with or without a profile - HPL / CPL laminate, a second plane with an anti-pressure film or HPL / CPL, and an uncovered edge - with or without an edge. The range of produced thickness from 8 mm to 40 mm or other, as agreed with the receiver</p>
Composition / information on the components	<p>Wood-based panel HDF sticker HPL / CPL laminate Back pressure foil Edge protecting the edge Urea glue for sticking back pressure film Polyacetate vinyl adhesive for gluing HPL/CPL laminate Hot melt adhesive for sticking edges Hot melt adhesive for sticking HDF stickers Polyurethane adhesive protecting the hydrophobic groove Manufactured product is free from halogenated compounds or wood preservatives.</p>
Storage	<p>Product should be stored in closed and dry spaces in accordance with – applicable storage instructions, health and safety and fire regulations. Personal protective equipment: protective gloves.</p>
Physical and chemical properties	<p>Coating requirements are specified by standards: ZN-1:2017, EN 438-3 Density depends on the thickness Colour depends on decorative finish Formaldehyde content meets the requirements of class E1, E1 E05 or actual IOS-MAT 0003/ IOS-MAT 0181 depending on the order.</p>
Impact on humans	<p>Product intended for furniture manufacturing and interior design. It may be used in permanent human dwellings.</p>
Transportation	<p>The product may be transported by any transport after providing protection against damage, moisture and displacement. The product may be safely transported when these conditions are met.</p>
Certificates and standards	<p>The material meets the requirements of the internal standard ZN-1: 2017 DUROPAL-HPL. Worktops and interior design elements and EN 438-3 High-pressure decorative laminates (HPL) - Plates of thermosetting resins (usually called laminates) - Part 3: Classification and specifications of laminates thinner than 2mm, intended to be connected to the carrier substrate (other requirements) Hygienic Certificate of the Institute of Maritime and Tropical Medicine in Gdańsk E1 Attestation E1 and CARB/TSCA Certificate of Wood Technology Institute in Poznan FSC/PEFC Certificate Health Certificate issued by National Institute of Public Health</p>
Fire classification	<p>Normally flammable Fire behaviour category (in line with EN 13986:2004+A1:2015): the product is not classified. Classification for the surface layer – high pressure laminate HPL: D-s2, d0 (EN 13501-1, CWFT acc. to 2003/593/EG)</p>
Environmental impact	<p>All waste under the code "03 01 05" in accordance with Polish law, has a component and properties that does not make it hazardous waste. They should be classified as non-hazardous waste within the meaning of the Act of December 14, 2012 on waste (Journal of Laws 2013.21) as amended and the Regulation of the Minister of Climate of January 2, 2020 on the waste catalog (Journal of Laws 2020, item 10). Wastes from mechanical treatment of materials under the code "03 01 05" should be subject to recovery or disposal in accordance with applicable regulations.</p>

As of 31.03.2021